

FDXCY SERIES

High Performance Flexible VSD Power Cable 0.6/1kV 90°C



APPLICATIONS:

VSD Connection Designed for the connection of AC Variable Speed Drives (VSD) or where a flexible EMC screened cable is required. These cables are flexible for fixed installation as well as occasional flexing without tensile load.

RFI & EMI Protection With double screening (CBS & foil tape) and split interstitial earth cores (6mm² and above), this cable has optimum screening performance of low frequency and electromagnetic output.

PRODUCT FEATURES:

- ▶ Helps avoid reactance with other devices outside the plant
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Moisture resistant
- ▶ Resistant to environmental factors such as oxidation, ozone and sunlight
- ▶ To be earthed using an EMC compatible gland
- ▶ Heat, oil and chemical resistant (*See Technical Section*)

CONSTRUCTION:

Conductor Annealed plain copper stranded high flexibility (Class 5).

Insulation X-90.

Screening 85% tinned copper braid screen c/w 100% foil screen coverage.

Sheath SPVC V-90.

CHARACTERISTICS:

Operating Temperature Range Fixed -20°C to 90°C / Flexing -5°C to 90°C.

Maximum Conductor Temperature 90°C (Current ratings are based on 30°C air temp. See technical section for de-rating factors).

Rated Voltage U_o/U 0.6/1kV.

Max AC Operating Voltage U_o 0.7kV.


Minimum Bending Radius 1.5mm² – 25mm²: Fixed 4 x cable diameter / Flexing 6 x cable diameter.

35mm² – 240mm²: Fixed 6 x cable diameter / Flexing 9 x cable diameter.

Sheath Colour Black.

Standard Core Colours Red, White, Blue, Green/Yellow.

Relevant Standards AS/NZS 5000.1, AS/NZS 1125, AS/NZS 3808, IEC 60332-1, **RoHS** Compliant.

Code	No. of Cores x Size		Approx. Stranding Power No. of wires x mm	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)	Nominal Amps un-enclosed protected from sun @ 30°C fixed application	3 Phase Volt Drop @ 50Hz / MAX. Conductor Temp:
	Power (mm ²)	Earth (mm ²)				Fixed Installation Touching 	90°C (Mv/Am)
FDXCY4/1.5	3x1.5 + 1 x 1.5		30/0.25	11.8	194	21	30.000
FDXCY4/2.5	3x2.5 + 1 x 2.5		50/0.25	12.7	250	29	16.400
FDXCY4/4.0	3x4.0 + 1 x 4.0		56/0.30	14.4	322	37	10.200
FDXCY4/6.0	3x6.0 + 3 x 1.5		84/0.30	15.7	406	47	6.800
FDXCY4/10	3x10 + 3 x 1.5		140/0.30	18.0	545	67	4.050
FDXCY4/16	3x16 + 3 x 2.5		126/0.40	20.1	789	89	2.550
FDXCY4/25	3 x 25 + 3 x 4.0		200/0.40	24.4	1154	119	1.62
FDXCY4/35	3 x 35 + 3 x 6.0		280/0.40	26.6	1503	149	1.18
FDXCY4/50	3 x 50 + 3 x 10		400/0.40	31.0	2167	187	0.878
FDXCY4/70	3 x 70 + 3 x 10		356/0.50	34.9	2817	235	0.623
FDXCY4/95	3 x 95 + 3 x 16		485/0.50	39.2	3816	282	0.467
FDXCY4/120	3 x 120 + 3 x 16		614/0.50	43.3	4498	333	0.385
FDXCY4/185	3 x 185 + 3 x 35		944/0.50	53.6	6859	436	0.285
FDXCY4/150	3 x 150 + 3 x 25		765/0.50	48.3	5684	383	0.330
FDXCY4/240	3 x 240 + 3 x 35		1225/0.50	59.9	8785	519	0.245

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.