DATA SHEET

CABLE LUBRICANT GEL

GEL 250 g / 1000 g

Item no.: RUNP30064





DATA			
ITEM NO.		RUNP30064	
CONTENT		1000 g	
WEIGHT		1,1 kg	
DIMENSION 1000 G	Height 26,5 cm / Width	h 8,5 cm	
EAN-CODE		9120045472318	

DESCRIPTION

Operational area:

RUNPOTEC cable lubricant GEL reduces the frictional resistance enormously, thus making it easier to pull cables and wires into electrical installation pipes and protecting them from cable damage.

Application:

Apply RUNPOTEC cable lubricant GEL to the cable or on the inside of the pipe. Also highly effective for the pushing in with cable pushing systems. To prevent staining, we recommend covering sensitive surfaces or removing excess lubricant directly with a damp cloth.

Product features:

Non-flammable, reduces frictional resistance, temperature resistant up to 85 °C, improved sliding effect, silicone-free, water-soluble, non-corrosive, no sticking, skin-friendly, biodegradable.

Dissolves without residue.

Caution: Seal after use, store in a cool and dry place.

Contact with live parts must be avoided

Risk of short circuit! EUH208: Contains 2 methyl-2H-isothiazole-3-one. Can cause allergic reactions. Staining possible on sensitive surfaces.

For instructions see safety data sheet!

Scope of delivery: 1 piece cable lubricant gel

ADVANTAGES

- ✓ Not flammable!
- No sticking, colourless and odourless
 Dissolves without residue
- Excellent sliding and lubricating effect

Product Code: RUNP30064

Supplied by Firstflex Cables www.firstflex.co.nz/runpotec