

# DATA SHEET

## GF3 Glass fiber Ø 3 mm

Cable pulling system for pipe diameter 10-50 mm

Item no.: RUNP10192 | RUNP10193 | RUNP10195



**CONTENT:** Accessory box (16-parts)



**INFO:**



**Front End:** Guiding head with swivel and RTG Ø 6 mm front thread with kink-protection



**Rear end:** Kink protection with RTG Ø 6 mm inner thread

DATA	RUNP10192	RUNP10193	RUNP10195
ITEM NO.			
LENGTH	20 m	30 m	50 m
TOTAL WEIGHT	1,28 kg	1,38 kg	1,58 kg
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	38 mm		
PIPE Ø	optimal from 10 mm - 50 mm		
DIMENSION	L: 295 mm x W: 245 mm x H: 74 mm		
EAN-CODE	9120045476729	9120045477122	9120045477139

### ADVANTAGES

- ✓ Integrated digital meter counter
- ✓ Guiding head with swivel and kink protection
- ✓ Autom. glide back protection
- ✓ Easy service access
- ✓ Extremely shockproof box
- ✓ Also for occupied pipes
- ✓ Including cable pulling loop
- ✓ Inspection camera RC2 compatible
- ✓ Total breaking load 130 kg

Rod	rec. pipe diameter	Bending radius w.e.joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	10 – 50 mm	38 mm	28 mm	450 kg	130 kg
0,118"	0,394" - 1,969"	1,102"	1,102"	992,08 lbs	286,60 lbs

### DESCRIPTION

GF3 - Cable pulling tool incl. digital meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with twist adjustment. Stowed in a shock-proof plastic box. The GF3 plastic box can be opened with only a single screw for service work. The glide-back protection prevents the fibreglass rod from accidentally slipping back into the box. Furthermore, the box has an ergonomic carrying handle and an anti-slip coating. The scope of delivery includes an 16-piece accessory set. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load of 130 kg refers to the glass fibre rod incl. kink protection joints. The cable pulling loop (Ø 14 mm outside) with built-in twist adjustment and protective cap included can be used for one or more cables up to a cable diameter of Ø 12 mm. Any plugs are protected by tensile load on the cable.

**Optimal field of application:** for pipe dimension 10 mm - 50 mm.

**Scope of supply:** 1 x GF3 incl. metre counter in plastic box, kink protection ending joint on both sides (start / end), contents of the accessory box: 1 x guiding head with twist adjustment, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pull-in aid, 1 x special adhesive 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive sleeves Ø 3 mm, 3 x pull eyes Ø 7 mm, 1 x starting bulb Ø 11 mm, 1 x connecting sleeve, 2 x mounting-wrench, 1 x button battery CR2032

### INFORMATION

**Compatible with:**

**RC2** inspection camera  
 Length: 10 m | 30 m | 50 m  
 Item no.: RUNP10139 |  
 RUNP10140 | RUNP10141



Supplied by Firstflex Cables  
[www.firstflex.co.nz/runpotec](http://www.firstflex.co.nz/runpotec)