


XB 500 APF - Adapter plate - Feet

for XB 500 and XB 500 T, load capacity 80 kg
Item no.: **RUNP20957**



DATA

Item No.	RUNP20957
DIMENSION	Ø 560 mm x H 50 mm
LOAD CAPACITY feet unfolded	80 kg
LOAD CAPACITY feet folded in	300 kg
WEIGHT	2,57 kg
EAN-Code	9120045477726
MATERIAL	Special plastic, stainless steel joints

DESCRIPTION

The XB 500 APF - Adapter plate - Feet can be connected to the XB 500 or XB 500 T professional cable roller. This enables optimal unwinding and rolling of pipe, cable bundles or cable drums on steel-laminated concrete ceilings during the construction phase. The adapter plate can be quickly connected to the XB 500 or XB 500 T and separated again using the fixing brackets and the quick-release lever on the underside. The four fold-out feet allow the XB 500 and XB 500 T to stand higher (21 cm) on the ceiling to be concreted, preventing it from slipping and ensuring trouble-free rolling. In this combination, the XB 500 and XB 500 T can hold up to 80 kg.

Optimum area of application: for optimum rolling and unrolling on steel-laminated concrete ceilings

Scope of supply: 1 x XB 500 APF - Adapter plate - Feet with 4 fold-out feet

ADVANTAGES

- Optimal for unwinding and rolling of pipe, cable bundles or cable drums on steel-laminated concrete ceilings
- The XB 500 or XB 500 T can be quickly connected and disconnected using the fixing brackets and the quick-release lever
- In combination with XB 500 and XB 500 T, loadable up to 80 kg

INFORMATION

Use with:

XB 500 and XB 500 T

Item no.: RUNP10136 | Item no.: RUNP10187



Product Code: RUNP20957

Supplied by Firstflex Cables
www.firstflex.co.nz/runpotec