

DATA SHEET

FIBREGLASS ROAD Ø 4,5 MM PROFI-SET

with steel cage incl. new double run-out system

Item no.: **RUNP10047**



Detailed image



BEGINNING



RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING



Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA

ITEM NO.				RUNP10047
LENGTH				60 m
TOTAL WEIGHT KG				5,025
DIMENSION	H 500 / B 380 / T 250			
MATERIAL	Fibreglass core with PP sheath			
PIPE Ø	for tube diameter 30 - 80 mm			
TOTAL BREAKING LOAD	220 kg			

ADVANTAGES

- ✓ incl. steel reel
- ✓ Double run-out system (automatic run-out brake and fast run-out)
- ✓ Additional parking brake
- ✓ Glass fibre rod total breaking load up to 1300 kg
- ✓ Total breaking load 220 kg
Bending radius 120 mm

Rec. tube diamter, bending radius and total breaking load for the fibreglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

DESCRIPTION

Professional set fibreglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

Optimal field of application: for pipe diameters 30 mm - 80 mm.

Scope of delivery: 1 piece fibreglass rod Ø 4.5 mm Profi Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the rod tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve, 1 x connecting sleeve, 1 x shackle, 1 x special adhesive, 1 x roller

Product Code: RUNP10047

Supplied by Firstflex Cables
www.firstflex.co.nz/runpotec