FIBREGLASS ROD Ø 6 MM PROFI SET

with steel cage incl. new double run-out system

Item no.: RUNP10065






DATA	
ITEM NO.	RUNP100
LENGTH	80 m
TOTAL WEIGHT KG	8,620
DIMENSION	H 570 / B 675/ T 250
MATERIAL	Fibreglass core with PP sheath
PIPE Ø	for tube diameter 40 - 100 mm
TOTAL BREAKING LOAD	320 kg

ADVANTAGES

- ✓ incl. steel reel
- ✓ **Double run-out system**(automatic run-out brake and fast run-out)
- ✓ Additional parking brake
- ✓ Glass fibre rod total breaking load up to 2200 kg
- √ Total breaking load 320 kg
- ✓ Bending radius 168 mm

Rec. tube diameter, bending radius and total breaking load for the fibreglass rod \emptyset 6 mm



DESCRIPTION

Professional set glass-fibre rod \varnothing 6 mm - RUNPOTEC RTG \varnothing 6 mm thread with robust steel reel \varnothing 530 mm (galvanised/powder coated) with new, double run-out system (automatic run-out brake and fast run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 2200 kg, total breaking load 320 kg

Optimal field of application: for pipe diameters 40 mm - 100 mm

Scope of delivery: 1 piece fibreglass rod \emptyset 6 mm Profi Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the road tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve,1 x connecting sleeve,1 x shackle,1 x special adhesive,1 x roller

Product Code: RUNP10065

Supplied by Firstflex Cables www.firstflex.co.nz/runpotec